

Suggested Supplies



Cutting Tools: Utility knife or most power cutting tools



Adhesives: Fuze*It by Liquid Nails construction adhesive or double sided mounting tape (not included)



Primers (required): Rust-Oleum® specialty plastic primer or equivalent



Paints (Optional): Compatible latex or oil-based paints


Additional Tools (Optional): Metal Ruler, Level, Paint Sprayer, Paint Brush, Masking Tape

1



Prepare the installation surface by cleaning it thoroughly.


2



Select a pattern for installation. Arrange it on the floor by rotating the tiles to preview or print out a pattern guide.


PERMANENT INSTALLATION

3




Apply a 1/4 inch adhesive bead to tile perimeter. Apply 1/4 in away from edge to prevent adhesive squeeze-out. Carefully remove and clean excess adhesive.

4




Use a level and a ruler to ensure tiles are properly aligned.

5




Apply tiles to surface, pressing each firmly, making sure that all corners are in contact with the surface.

6




Allow adhesive to dry (following adhesive manufacturers instructions).

7 (optional)



Use Fuze*It to seal the seams. Clean up and smooth as you go along before it sets. Tiles should not be sanded. 8 (required for painting tiles)



Coat tiles once with plastic primer first and then with the finish of your choice.




3

TEMPORARY INSTALLATION


Coat each tile with plastic primer first and then the finish of your choice.

4




Apply the selected adhesion method to the perimeter and the center of tile when possible. We recommend 3M mounting tape.

5




Apply tiles to surface pressing each tile firmly. Make sure that all edges are in contact with the surface and that tiles are securely adhered.




PlasticForms can be installed on a canvas or a thin plywood frame for ease of installation, transportation and finishing.


GENERAL



Make your installation last by applying tiles at a height that makes sense for the environment. Prevent tile damage and keep your PlasticForms looking beautiful.



Tiles should be dusted or vacuumed regularly. Use a damp cloth or sponge to clean tiles.



Follow the manufacturers recommended removal directions for each adhesive material. Remove tiles gently to minimize damage to surfaces.

MIOCULTURE.COM





All trademarks, service marks and trade names (MIO, product names and the MIO logo) are owned and registered by MIO. All content including but not limited to text, designs, graphics, photos and all other content ("Content") is a collective work under the United States and other copyright laws and is the proprietary property of MIO. All rights reserved. @2025 MIOOIM LLC

Still have questions? Drop us a line or give us a call:

Email: info@mioculture.com US Toll Free: 1 - 888 - 563 - 3916 International: +1 (215) 925 - 9359